

# MICROCEMENT PRIMER N-ABS HARDENER



**FAMILY** ALTA DECORACION  
**LINE** DECO MICROCEMENTO

## DESCRIPTION AND NATURE

MICROCEMENT PRIMER N-ABS HARDENER

## USAGES

Outdoors/Indoors

## PROPERTIES

- Drying fast

## TECHNICAL CHARACTERISTICS

|                                 |                                                   |
|---------------------------------|---------------------------------------------------|
| Referencia Color                | MICROCEMENT PRIMER N-ABS HARDENER                 |
| Mixture relation                | 2 MICROCEMENT PRIMER N-ABS : 1 N-ABS HARDENER (w) |
| Finish                          | .                                                 |
| Specific weight                 | 1,08± 0,05 kg/l                                   |
| Solids in volume                | 100± 1                                            |
| Solids in weight                | 100± 1                                            |
| Aproximated performance by coat | Depending of product usage                        |

## SURFACE PREPAIRING

### New surfaces

See the MICROCEMENT PRIMER N-ABS technical data sheet

### Restoring and maintenance

See the MICROCEMENT PRIMER N-ABS technical data sheet

## WAY OF USE

### Application notes

The product on this technical file has the indicated lifespan if it is stored in a dry place at a temperature between 5°C and 35°C in the original package.

The product can crystallise at low temperatures and, in that case, can be recovered by heating it at 50°C followed by stirring. In this way, it does not lose its characteristics and maintains its values and properties.

### Solvent for dilution and cleaning

**Way of use**                      **Aproximate dilution**

## SYSTEM

### Procedures depending of surface type

**Primer**

**Intermedium**

**Finish**

# MICROCEMENT PRIMER N-ABS HARDENER

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

1 Kg