

Fecha de Alta

26-06-2007

Versión

7 - 27/10/2025

**FAMILY**

MADERA

LINE

ACEITES

DESCRIPTION AND NATURE

High-quality linseed oil with drying additives. Creates a light, waterproof layer. For nourishing and adding shine to all types of raw wood.

USAGES

Indoors/Outdoors

Wood

Penetrates, protects and nourishes wood

PROPERTIES

- Gloss
- Elasticity
- Penetrating depth
- To avoid putrefaction
- Non-plumbing dryers addition
- Easily applicable
- Highlights shade

TECHNICAL CHARACTERISTICS

Referencia Color ACEITE DE LINAZA

Finish Transparent

Specific weight (0,88 ± 0,03)g/mL

Viscosity (40 ± 10)s

Solids in volume (58 ± 1)

Solids in weight (63 ± 1)

Aproximated performance by coat 10-14 m²/L

Dry to touch (20°C HR:60%):24-48h

Dry to repaint (20°C HR:60%):>24h

Colours Colorless

Montomix Base: Pine, Teak, Walnut

SURFACE PREPAIRING**New surfaces**

New Wood:

- The substrate must be free of foreign matter and/or residue.
- Apply to wood with a moisture content of less than 20%.
- Apply to healthy, well-degreased, dust-free, and dry wood.
- For wood with resin stains on the interior (usually conifers) and/or oily tropical woods, it will be necessary to first clean them with solvent.
- If the wood shows signs of aging, it should be sanded first, removing all grayed surfaces and removing dust by brushing or other mechanical means.
- Spread the oil with a trowel or roller and wait 15-30 minutes. In areas with greater absorption, redistribute the excess product. Repeat the process until the piece is saturated with oil.
- Remove any excess.

Fecha de Alta

26-06-2007

Versión

7 - 27/10/2025

Restoring and maintenance

Oiled Wood:

- Loss of shine over time indicates deterioration of the oil.
- Repeat the process to renew the appearance and protection at this point.

WAY OF USE**Application notes**

1. General:

- Stir the product until completely smooth.
- Apply to clean, dry substrates.
- Sand beforehand to ensure good penetration and evenness on the wood.
- Apply following the dilutions recommended in the Application Systems section.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply when relative humidity is above 80%.
- Clean wood with resins and/or exotic oils first with solvent.
- Remove any excess residue from the surface.

2. Warning:

- Remains of fabric, paper, etc., that have been stained with traces of natural oils or drying agents may spontaneously combust. They must be soaked with water before disposal.

Solvent for dilution and cleaning

Solvent 1401, Solvent 1413; Cleaning Solvent 1406

Way of use	Aproximate dilution
Painting brush	0-10%
Roller	0-10%
Cloth	0-10%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Wood			
MAX	Aceite de linaza diluido	Aceite de linaza diluido	Aceite de linaza diluido
STD	Aceite de linaza diluido		Aceite de linaza diluido

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

501305

ACEITE DE LINAZA



Fecha de Alta

26-06-2007

Versión

7 - 27/10/2025

PACKINGS

1 L, 5 L