



FAMILY

MADERA

LINE

TRATAMIENTO CARCOMA

DESCRIPTION AND NATURE

Treatment of the woodworm with certificate of effectiveness. Preventive use.

Protection against wood destroying fungi.

Broad spectrum for the conservation of wood. For new and used wood, out of contact with soil and water.

In all cases it is necessary to coat with a finished product.

USAGES

- Protection of any type of wood, especially outdoors
- In new and used woods. Especially suitable for outdoor applications.
- Outdoors, in woods subject to risk class 3.
- Outdoor / Indoor
- Wood after varnished
- Improves adhesion to subsequent layers
- Wood treatment
- Suitable for woodwork, doors, windows, moldings, etc.
- Surface treatment wood for woodworm
- Environmental use: Only specialized staff
- Use for general public

PROPERTIES

Optimal applicability

Fungicide, effective against blue stain in conifers.

Excellent weather resistance

EN 118 Determination of the preventive efficacy against termites of the *reticulitermes* genus, together with the evaporation poisoning according to EN73 and washout according to EN 84

EN 46: Determination of efficacy against insects after aging test by evaporation EN 73 and by washout EN 84

EN 113: Determination of humbral efficacy against basidiomycete fungi, after aging test by evaporation EN 73 and washout EN 84. EN 73 and by washout EN 84

EN 152 Determination of preventive efficacy against blueing

Delay putrefaction. Preventive to the attack of fungi and bluish insect

In case of accident, consult the Medical Toxicological Information Service: 915620420

TECHNICAL CHARACTERISTICS

Referencia Color ANTICARCOMA KLEARXYL DI

Finish Transparent

Specific weight 0,78 ± 0,05 kg/l

Solids in volume 8 ± 1

Solids in weight 8 ± 1

Aproximated performance by coat 3-5 m²/L

Dry to touch (20°C HR:60%):30-60min

Dry to repaint (20°C HR:60%):24h

Colours Transparent

SURFACE PREPAIRING

New surfaces

On uncontaminated wood, usable as a preventive (See Technical Characteristics).

Fecha de Alta

12-01-2017

Versión

4 - 20/08/2024

General precautions in application conditions:

- During application and drying, the temperature must be above 5°C and the relative humidity below 80%.
- When applying the product, the moisture content of the wood should not exceed 18% and the surface of the wood should be dry, clean and free of any rot at the time of treatment.

Restoring and maintenance

On uncontaminated wood, remove varnish and use as a preventative. (See Technical Characteristics).

General precautions in application conditions:

The same as for new supports.

WAY OF USE**Application notes**

Homogenize the product slowly using a spatula.

Open pore using sandpaper (40-80) for wood.

"In order to avoid risks to people and the environment, follow the instructions for use"

Before using the product, read the label carefully.

Do not apply to food or kitchen utensils.

Do not use in the presence of people or pets.

Adequately ventilate the area where the product is applied.

Solvent for dilution and cleaning

Solvent 1401

Way of use	Aproximate dilution
Painting brush	0
Roller	0

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
New wood indoor / outdoor			
MAX	Anticarcoma Klearxyl di	Productos familia 5 Gama Madera y CREA	Productos familia 5 Gama Madera y CREA
STD	Anticarcoma Klearxyl di		Productos familia 5 Gama Madera y CREA
Paints and watter lasures			
MAX	Decapar, lijar y Anticarcoma Klearxyl di	Productos familia 5 Gama Madera y CREA	Productos familia 5 Gama Madera y CREA
STD			
Montoxyl range			
MAX	Anticarcomas Klearxyl di	Anticarcomas Klearxyl di	Productos familia 5 Gama Madera y CREA
STD	Anticarcomas Klearxyl di		Productos familia 5 Gama Madera y CREA
Polyurethane lacquers and varnishes			
MAX	Decapar, Lijar, Anticarcoma Klearxyl di	Productos familia 5 Gama Madera	Productos familia 5 Gama Madera
STD	Decapar, Lijar, Anticarcoma Klearxyl di		Productos familia 5 Gama Madera
Nitrocellulose lacquers and varnishes			
MAX	Decapar, Lijar, Anticarcoma Klearxyl di	Productos familia 5 Gama Madera	Productos familia 5 Gama Madera
STD	Decapar, Lijar, Anticarcoma Klearxyl di		Productos familia 5 Gama Madera

Fecha de Alta

12-01-2017

Versión

4 - 20/08/2024

Enamels and synthetic varnishes

MAX	Decapar, Lijar y Anticarcoma Klearxyl di	Productos familia 5 Gama Madera	Productos familia 5 Gama Madera
STD	Decapar, Lijar y Anticarcoma Klearxyl di		Productos familia 5 Gama Madera

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 2.5 L