

Fecha de Alta

26-02-2020

Versión

6 - 03/11/2025



FAMILY
LINE

PAREDES Y TECHOS
SATINADA

DESCRIPTION AND NATURE

Ideal for applying plastic paint on white vinyl media. Good resistance to sunlight. Applicable on building materials and wood.

USAGES

Indoors/Outdoors
Walls and ceilings
Cement mortars
Concrete
Brick
Plaster
Dripping effect
Drywall (gypsum plasterboard): fibreboard

PROPERTIES



Gloss level: satin (according to UNE-EN 13300, at 60° the reflectance <60 and at 85° the reflectance > 10 (35 ± 5)

Washability: Class 1 (according to Standard UNE-EN 13300)

Opacity: Class 2 for a performance of 6 m²/litre (according to Standard UNE-EN 13300)

TECHNICAL CHARACTERISTICS

Referencia Color	NEVADA SATINADO BLANCO
Finish	.
Specific weight	1,22± 0,05 kg/l
Viscosity	140 +/- 20 PO
Solids in volume	36± 1
Solids in weight	49± 1
VOC	Cat. b/BA 150/100 (2007/2010):19,61 g/l
Aproximated performance by coat	11-13 m ² /L
Dry to touch	(20°C HR:60%):1h
Dry to repaint	(20°C HR:60%):3-4h
Colours	White. Colours with water Montotinte Universal máx. 5%.
Classification	AFNOR: NFT. 36005 Famille I Classe 7b2

SURFACE PREPAIRING

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Very damaged surfaces should be fixed with suitable product.
- Use Emulsión Fijadora like primer to prevent "sheen".
- Cover surface imperfections with Plastmont Exteriores (See Family 6).

Fecha de Alta

26-02-2020

Versión

6 - 03/11/2025

- Plaster:
- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product (See Family 6).
- Use Emulsión Fijadora like primer to prevent "sheen".
- Cover surface imperfections with plaster or putty (See Family 6).

Restoring and maintenance

1. Remove off old paint completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring in painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty of plaster (See Family 6 to help you choose the most suitable product to prepare surfaces).
5. Use Emulsión Fijadora like primer to prevent "sheen".
6. Mildewed surfaces should be treated with Monto Limpia Moho.

WAY OF USE**Application notes**

- Product should shaken until perfectly homogenized.
- Product should be diluted depending on surface porosity and condition on first layer.
- Finish with one or more layers slightly diluted until total surface covering.
- Do not apply product at temperatures under 5° or on any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	10-25%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Inner painted old work in good state			
MAX			
STD	Nevada Satinado diluée		Nevada Satinado
Old paintings Lime			
MAX	Eliminer + fixateur	Nevada Satinada	Nevada Satinada
STD	Eliminer + Nevada Satinada diluée		Nevada Satinada
Works			
MAX	Fixateur	Nevada Satinado	Nevada Satinado
STD	Nevada Satinado diluée		Nevada Satinado
Drywall (gypsum plasterboard)			
MAX	Nevada Satinado diluée	Nevada Satinado	Nevada Satinado
STD	Nevada Satinado diluée		Nevada Satinado

Fecha de Alta

26-02-2020

Versión

6 - 03/11/2025

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L