

Fecha de Alta

31-10-2007

Versión

4 - 23/08/2024



FAMILY

ESMALTES

LINE

ANTIOXIDANTE METALES

DESCRIPTION AND NATURE

Recommended solvent for thinning and cleaning our Ferrorite line of anti-oxidants.

USAGES

Essential for dilution of Ferrorite Esmalte Martelé

Recommended for Ferrorite Esmalte liso y forja. Regulator application viscosity in products Ferrorite.

PROPERTIES

Specific odour

Suitable evaporation velocity, obtaining a perfect balance between external and internal drying

When added in adequate proportions, do not change final product properties

Water and alcohol free

TECHNICAL CHARACTERISTICS

Referencia Color	FERRORITE DISOLVENTE
Specific weight	0,83± 0,05 kg/l
Solids in volume	0 ± 1
Solids in weight	0 ± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	-
Dry to repaint	-
Colours	Transparent

SURFACE PREPAIRING

New surfaces

Proceed following the paint instructions in which this product is recommended.

Restoring and maintenance

Proceed following the paint instructions in which this product is recommended.

WAY OF USE

Application notes

- As a viscosity regulator:
- Add on top of Ferrorite, in the proportion stated in the specifications sheet of the product to be diluted.
- Slowly stir the previous mix with a spatula until you get a smooth mixture.
- As a tool cleaning solvent:
- Clean tools immediately after use until all Ferrorite has completely disappeared.
- Then wash with soapy water and dry immediately after washing.

Solvent for dilution and cleaning

Way of use

Aproximate dilution

Fecha de Alta

31-10-2007

Versión

4 - 23/08/2024

SYSTEM**Procedures depending of surface type**

Primer

Intermedium

Finish

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.25 L, 0.75 L, 5 L