

PLASMONT BRICOLAGE CEMENTO COLA



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS EN POLVO

DESCRIPTION AND NATURE

Cement in powder form for exteriors. Incorporates great adherence additives for any type of surface. Ideal to secure tiles, marbre, ceramic etc.

USAGES

Outdoors/Indoors
Brick
Ceramic material
Marble
Masonry repair

PROPERTIES

Strongness
Able to be sanded
Good adhesion
Fast hardening
Smooth rugged touch

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT BRICOLAGE CEMENTO COLA
Mixture relation	200-250 ml de agua/kg de masilla
Finish	Matt
Specific weight	2,63± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 2-3h
Dry to repaint	(20°C HR: 60%): 24h
Colours	Beige

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

-Test CEMENT MORTER suitability on surface.

-Remove off any efflorescences through abressive jet and neutralize alkaline surfaces.

-Extremely polished surfaces should be treated to open pores.

-Remove off any foreing remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brush and apply CEMENTO COLA as indicated under Application Systems and Application points.

-For extremely damaged surfaces, use suitable fixer (see family 6) .

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

PLASMONT BRICOLAGE CEMENTO COLA

WAY OF USE

Application notes

- Dilute only with fresh water.
- Use only clean and rust-free indicated tools under "Application Systems"
- Bad condition surfaces should be anchored with Fijamont, Emulsion Fijadora or Fijalite products.
- Only repaint after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
- Adhesive to join marbre, tiles and brick pieces.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Palette / spatula

Palette

Aproximate dilution

200-250 ml de agua por 1 kg de masilla

200-250 ml de agua por kg de masilla

200-250 ml de agua por 1 kg de masilla

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX			Familias 1, 2, 4
STD	Cemento cola	Fijador(Emulsión Fijadora, Fijamont)	

Laying of bricks, floor tiles or marble

MAX	Directamente sobre cemento	Baldosas, ladrillo, mármol
STD		

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE


Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1.5 Kg

PLASMONT BRICOLAGE CEMENTO COLA



FAMILY LINE

DESCRIPTION AND NATURE

Cement in powder form for exteriors. Incorporates great adherence additives for any type of surface. Ideal to secure tiles, marbre, ceramic etc.

USAGES

PROPERTIES

Strongness
Able to be sanded
Good adhesion
Fast hardening
Smooth rugged touch

TECHNICAL CHARACTERISTICS

Referencia Color	
Mixture relation	200-250 ml de agua/kg de masilla
Finish	Matt
Specific weight	2,63± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 2-3h
Dry to repaint	(20°C HR: 60%): 24h
Colours	Beige

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

- Test CEMENT MORTER suitability on surface.
- Remove off any efflorescences through abressive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be treated to open pores.
- Remove off any foreing remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brush and apply CEMENTO COLA as indicated under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) .

Restoring and maintenance


Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.
Test adherence level and treat as per new surfaces.

WAY OF USE

Application notes

- Dilute only with fresh water.
- Use only clean and rust-free indicated tools under "Application Systems"

PLASMONT BRICOLAGE CEMENTO COLA



- Bad condition surfaces should be anchored with Fijamont, Emulsion Fijadora or Fijalite products.
- Only repaint after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
- Adhesive to join marbre, tiles and brick pieces.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Pallette

Aproximate dilution

200-250 ml de agua por 1 kg de masilla

200-250 ml de agua por kg de masilla

200-250 ml de agua por 1 kg de masilla

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX			Familias 1, 2, 4
STD	Cemento cola	Fijador(Emulsión Fijadora, Fijamont)	

Laying of bricks, floor tiles or marble

MAX	Directamente sobre cemento	Baldosas, ladrillo, mármol
STD		

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

1.5 Kg