

PLASMONT BRICOLAGE CEMENTO RAPIDO



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS EN POLVO

DESCRIPTION AND NATURE

Quick cement in powder form. To secure and repair joints, where quick drying is needed.

USAGES

Outdoors/Indoors

Plaster finishing

PROPERTIES

Strongness
High and medium thickness finishings
Good adhesion
Fast hardening
Smooth rugged touch

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT BRICOLAGE CEMENTO RAPIDO
Mixture relation	500 ml de agua por kg de masilla
Finish	Matt
Specific weight	2,91± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 1-2h
Dry to repaint	(20°C HR: 60%): 24 days
Colours	Beige

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

- Test CEMENT RAPID suitability on surface.
- Wait till complet drying of product before top coat.
- Remove off any efflorescences through abressive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brush and apply CEMENTO RAPIDO as indicated under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) .

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

PLASMONT BRICOLAGE CEMENTO RAPIDO

WAY OF USE

Application notes

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.
- Only repaint after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallete / spatula

Pallete

Aproximate dilution

500 ml de agua por kg de masilla

500 ml de agua por kg de masilla

500 ml de agua por kg de masilla

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX	Cemento rápido		
STD		Fijador (Emulsión fijadora, Fijamont)	Monto plásticas, Revestimientos, Esmaltes

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1.5 Kg




**FAMILY
LINE**

DESCRIPTION AND NATURE

Quick cement in powder form. To secure and repair joints, where quick drying is needed.

PLASMONT BRICOLAGE CEMENTO RAPIDO



USAGES

PROPERTIES

Strongness
High and medium thickness finishings
Good adhesion
Fast hardening
Smooth rugged touch

TECHNICAL CHARACTERISTICS

Referencia Color	
Mixture relation	500 ml de agua por kg de masilla
Finish	Matt
Specific weight	2,91 ± 0,05 kg/l
Solids in volume	100 ± 1
Solids in weight	100 ± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 1-2h
Dry to repaint	(20°C HR: 60%): 24 days
Colours	Beige

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

- Test CEMENT RAPID suitability on surface.
- Wait till complet drying of product before top coat.
- Remove off any efflorescences through abressive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brush and apply CEMENTO RAPIDO as indicated under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) .

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.
Test adherence level and treat as per new surfaces.

WAY OF USE

Application notes

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.
- Only repaint after indicated drying time, which depends on moistering and temperature conditions as well as layer thickness.

Solvent for dilution and cleaning

Water

PLASMONT BRICOLAGE CEMENTO RAPIDO

Way of use

Stainless trowel

Pallette / spatula

Pallette

Aproximate dilution

500 ml de agua por kg de masilla

500 ml de agua por kg de masilla

500 ml de agua por kg de masilla

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Project			
MAX	Cemento rápido		
STD		Fijador(Emulsión fijadora, Fijamont)	Monto plásticas, Revestimientos, Esmaltes

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE**PACKINGS**

1.5 Kg