



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS EN POLVO

DESCRIPTION AND NATURE

Product in powder form to prepare with water. To repair plastering and securing pipes, wires etc. Quick drying.

USAGES

Indoors
Cement
Plaster
Brick
Tiles
Wood
Concrete
Dripping effect
Plaster

PROPERTIES

Adherence
Easy sandable
Fast hardening

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT BRICOLAGE YESO
Finish	Matt
Specific weight	2,25± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Minimum recommended thickness	3mm por capa
Aproximated performance by coat	Depending of product usage

Dry to repaint	(20°C HR: 60%): 20 days
Colours	White

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

- Test putty suitability on surface.
- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences through abrassive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be treated to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply putty as indicated under Application Systems and Application points.
- Do not apply product in extremely thick layers.
- For extremely damaged surfaces, use suitable fixer (see family 6): Emulsion Fijadora, fijamont or Fijalite before applying putty.

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.
Test adherence level and treat as per new surfaces.

Fecha de Alta

13-04-2007

Versión

4 - 18/09/2024

WAY OF USE

Application notes

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Surfaces should be anchored properly.
- Repaint only after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
- Can be dried mechanically.
- Ovaldine, Montoplastica, Montoature, Esmalte Montosintetic, Luxatin and Select Decoration products are suitable for top coats.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Pallette

Aproximate dilution

400ml agua por kg de masilla

400ml agua por kg de masilla

400ml agua por kg de masilla

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX	Yeso		
STD		Emulsión Fijadora, Fiajmont	Productos de la familia 1, 4 o 12

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg

**FAMILY
LINE****DESCRIPTION AND NATURE**

Product in powder form to prepare with water. To repair plastering and securing pipes, wires etc. Quick drying.

USAGES**PROPERTIES**

Adherence
Easy sandable
Fast hardening

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight 2,25± 0,05 kg/l

Solids in volume 100± 1

Solids in weight 100± 1

Minimum recommended thickness 3mm por capa

Aproximated performance by coat Depending of product usage

Dry to repaint (20°C HR: 60%): 20 days

Colours White

SURFACE PREPAIRING**New surfaces**

Plaster and mortar cement:

- Test putty suitability on surface.
- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences through abressive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be treated to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply putty as indicated under Application Systems and Application points.
- Do not apply product in extremely thick layers.
- For extremely damaged surfaces, use suitable fixer (see family 6): Emulsion Fijadora, fijamont or Fijalite before applying putty.

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems.
Test adherence level and treat as per new surfaces.

WAY OF USE**Application notes**

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Surfaces should be anchored properly.

Fecha de Alta

13-04-2007

Versión

4 - 18/09/2024

-Repaint only after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
-Can be dried mechanically.
-Ovaldine, Montoplastica, Montoature, Esmalte Montosintetic, Luxatin and Select Decoration products are suitable for top coats.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Pallette

Aproximate dilution

400ml agua por kg de masilla

400ml agua por kg de masilla

400ml agua por kg de masilla

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
--	--------	-------------	--------

Project**MAX** Yeso**STD**

Emulsión Fijadora, Fiajmont

Productos de la familia 1, 4 o 12

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE**PACKINGS**

1 Kg