

Fecha de Alta

26-06-2007

Versión

6 - 19/08/2024



**FAMILY**  
**LINE**

**MADERA**  
**ACEITES**

### DESCRIPTION AND NATURE

High quality linseed oil with drying additives, for use as a wood protector, impregnating agent and sealer

### USAGES

Outdoors/Indoors

Wood

### PROPERTIES

Elasticity  
Penetration power  
Sun & rain protective  
To avoid putrefaction  
Non-plumbing dryers addition  
Highlights shade

### TECHNICAL CHARACTERISTICS

Referencia Color	ACEITE DE LINAZA
Finish	Transparent
Specific weight	0,86± 0,05 kg/l
Viscosity	41 +/- 15 SG
Solids in volume	0± 1
Solids in weight	63± 1
Aproximated performance by coat	8-12 m²/L
Dry to touch	(20°C HR: 60%): 24-48h
Dry to repaint	(20°C HR: 60%): >24h
Colours	Candy. Tintable with Montotinte max 5%.

### SURFACE PREPAIRING

#### New surfaces

New woods:

- The support must be free of foreign products and/or residues.
- Apply to wood with a moisture content of less than 20%.
- Apply to healthy, well-degreased, dust-free and dry wood.
- Sand and eliminate possible traces of glue in the assemblies and machining errors.
- If the wood shows signs of aging, it must be previously sanded and dust removed by brushing or any other mechanical means.
- By spray, the most recommended means of application is the Airless System.

#### Restoring and maintenance

Varnished or painted wood:

- If they have been varnished with Montoxyl Color, remove foreign products, eliminate poorly adhered areas or areas in poor condition, sand lightly, eliminate the dust resulting from sanding and proceed as with new wood.
- If they have been varnished with closed-pore varnishes such as Matte Universal Synthetic Varnish (Code: 1350), Satin or Glossy, Sailboat Varnish, High Mountain Varnish or similar, remove blisters, edge lifting or cracks by stripping them with Quitamont. If the surface is in good condition, sand lightly, remove the dust resulting from sanding and proceed as with new

Fecha de Alta

26-06-2007

Versión

6 - 19/08/2024

wood.

- If they have been varnished with cellulose varnishes or polyurethanes, remove them by stripping with Quitamont Universal (Code: 3510) or by mechanical means and proceed as with new wood.

- If they have been glazed with synthetic enamel (Montosintetic Code: 2020, 2024), Marisma (Code: 2010, 2014), Luxatín (Code: 2028) or similar, remove by stripping with Quitamont Universal (Code: 3510) or by mechanical means and Proceed as with new wood.

## WAY OF USE

### Application notes

Stir the product until it is perfectly homogenized.

Apply in supply form.

Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions during drying time.

Do not apply with relative humidity greater than 80%.

Review periodically and perform maintenance regularly.

### Solvent for dilution and cleaning

Solvent 1401-13

Way of use	Aproximate dilution
Painting brush	0-10%
Roller	0-10%
Air-less gun	10-20%
Air-mix gun	10-20%
Aerographic gun	10-20%
Low pressure turbo	10-20%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Wood</b>			
<b>MAX</b>	Aceite de linaza diluido	Aceite de linaza diluido	Aceite de linaza diluido
<b>STD</b>	Aceite de linaza diluido	Aceite de linaza diluido	Aceite de linaza diluido

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

1 L, 5 L