

**FAMILY**  
**LINE**

MADERA

MUEBLE (LACAS POLIURETANO)

**DESCRIPTION AND NATURE**

Aromatic hardener. For transparent Montopol Range polyurethanes and pigmented primers. To keep the color of the finishes unchanged, use the Montopol NA Hardener.

**USAGES**

Inside  
Solid Wood and Veneer  
Reactive mixture for the Montopol range products

**PROPERTIES**

Strongness  
Elasticity  
Resistance to the chemical attacks  
Pot life

**TECHNICAL CHARACTERISTICS**

|                                 |                            |
|---------------------------------|----------------------------|
| Referencia Color                | CATALIZADOR MONTOPOL MS    |
| Mixture relation                | Ver parte A                |
| Finish                          | Transparent                |
| Specific weight                 | 0,94± 0,05 kg/l            |
| Viscosity                       | 12 +/- 2 SG                |
| Solids in volume                | 27± 1                      |
| Solids in weight                | 32± 1                      |
| Aproximated performance by coat | Depending of product usage |
| Colours                         | Colourless                 |

**SURFACE PREPAIRING****New surfaces**

New wood:

- Follow the instructions for the Montopol Range product to be catalysed.

**Restoring and maintenance**

Varnished or painted wood:

- Follow the instructions for the Montopol Range product to be catalysed.

**WAY OF USE****Application notes**

Mix without modifying under any circumstances the proportions of part A (Montopol Range Product), with part B (Montopol MS hardener)  
Mix with the indicated product by manually stirring with a wooden, metal or glass spatula, in a well-ventilated space, leaving it to rest for a few minutes

Fecha de Alta

13-04-2007

Versión

1C - 20/08/2024

**Solvent for dilution and cleaning**

Solvent 1410

**Way of use****Aproximate dilution****SYSTEM****Procedures depending of surface type****Primer****Intermedium****Finish****SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

2.2 Kg, 11 Kg, 0.375 L, 2.5 L, 12.5 L