

Fecha de Alta

13-04-2007

Versión

1C - 20/08/2024

**FAMILY**

MADERA

LINE

MUEBLE (LACAS POLIURETANO)

DESCRIPTION AND NATURE

Aliphatic hardener (non-yellowing). To catalyze the Montopol Range white finishes and pastel colors and/or sensitive to yellowing over time that come from the transparent Montopol Range.

USAGES

Inside

Solid Wood and Veneer

PROPERTIES

Strongness

Elasticity

Resistance to the chemical attacks

Resistance to the yellowness

Pot life

Formulated as hardener of white Montopol topcoat BL range

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR MONTOPOL NA
Mixture relation	Ver parte A.
Finish	Transparent
Specific weight	0,92± 0,05 kg/l
Viscosity	10 +/- 2 SG
Solids in volume	21± 1
Solids in weight	26± 1
Aproximated performance by coat	Depending of product usage

Colours	Colourless
---------	------------

SURFACE PREPAIRING**New surfaces**

New woods:

- Follow the instructions of the product range Montopol catalyze.

Restoring and maintenance

Varnished or painted wood:

- Follow the instructions of the product range Montopol catalyze.

WAY OF USE**Application notes**

Mix without modifying under any circumstances the proportions of part A (Montopol Range Product), with part B (Montopol NA hardener)

Mix with the indicated product by manually stirring with a wooden, metal or glass spatula, in a well-ventilated space, leaving it to rest for a few minutes

Fecha de Alta

13-04-2007

Versión

1C - 20/08/2024

Solvent for dilution and cleaning

Solvent 1410

Way of use**Aproximate dilution****SYSTEM****Procedures depending of surface type****Primer****Intermedium****Finish****SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

2 Kg, 10 Kg