

Fecha de Alta

09-01-2020

Versión

3 - 12/08/2024



FAMILY
LINE

PAREDES Y TECHOS
MATE PREMIUM

DESCRIPTION AND NATURE

Washable white paint that gives great white coverage for walls and ceilings. Easy to apply, high performance, ideal for interior decoration in general, particularly for achieving smooth finishes with good results.

USAGES

Indoors/Outdoors
Walls and ceilings
Cement mortars
Concrete
Brick
Plaster
Dripping effect
Drywall (gypsum plasterboard): fibreboard

PROPERTIES



With anti-mould additive

Gloss level: extra matt (according to 13300 standard, at 85° reflectance <5)

Washability: Class 2 (according to Standard UNE-EN 13300)

No dripping or splashes (Tixoleless Technology)

Opacity: Class 1 for a performance of 5.5 m²/litre (according to Standard UNE-EN 13300)

TECHNICAL CHARACTERISTICS

Referencia Color	MAGNUM BLANCO
Finish	.
Specific weight	1,5± 0,05 kg/l
Viscosity	65 +/- 10 PO
Solids in volume	40± 1
Solids in weight	62± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,12 g/l
Aproximated performance by coat	13-15 m ² /L
Dry to touch	(20°C HR:60%):1h
Dry to repaint	(20°C HR:60%):3-4h
Colours	White

SURFACE PREPAIRING

New surfaces

Cement and concrete mortars:

1. Wait until fully set (min. 30 days).
2. Clean any efflorescence with a jet washer.
3. Neutralize alkaline surfaces.
4. Sand polished surfaces to create a rougher surface.
5. Clean the surface to remove foreign products.
6. Set crumbly substrates with Fixer Emulsion or Fijamont.

Fecha de Alta

09-01-2020

Versión

3 - 12/08/2024

7. Fill in defects in the substrate (see family 6)

Plaster, plaster-covered brick:

1. Wait until it is completely dry (max. 20% humidity).
2. Clean the surface to remove foreign products.
3. Clean any efflorescence with a jet washer.
4. Regulate surface absorption with sealer, fixer, or a diluted coat of the same product
5. Sand polished surfaces to create a rougher surface
6. Set crumbly substrates with Fixer Emulsion or Fijamont.
7. Fill in defects in the substrate (see family 6)

Plasterboard partition walls:

1. Carry out a general sanding of the joints and putty fixing areas.
2. Then, clean them to ensure the substrate is free of dust, grease and other contaminants.
3. For application on coloured boards that tend to generate stains, apply Monoplac Stain-Resistant Sealer.

Restoring and maintenance

1. Completely remove old paint that is in poor condition or that is poorly-adhered.
2. Glossy surfaces should be thinned out to ensure good adhesion.
3. On painted surfaces, check that the paint is solid and well-adhered. Its condition must be assessed, in order to avoid possible incompatibilities. Dust and dirt must also be eliminated before repainting.
4. Apply filler (Plasmont) to any defects on the surface.
5. Pre-treat mouldy walls using Monto Limpia Moho.

WAY OF USE**Application notes**

- Shake the product until it is perfectly homogenised.
- For the first coat, dilute the product according to the porosity and state of the surface.
- Finish with one or more lightly diluted coats until the surface is completely covered.
- Do not apply the product at temperatures below 5° or on surfaces exposed to strong sunshine.
- Do not wash for the first 24 days.
- Never apply it outdoors if there is an imminent risk of rain, and avoid excessively wet days.
- Clean tools with water immediately after use.
- For spraying with Airless equipment, use 15 to 23 inch nozzles, pressure \approx 150 bar.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-5%
Roller	0-5%
Air-less gun	5-15%
Air-mix gun	5-15%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Inner painted old work in good state			
MAX			
STD	Magnum Diluido		Magnum
Inner painted old work in good state			
MAX	Eliminar + Fijador	Magnum	Magnum
STD	Eliminar + Magnum Diluido		Magnum
Project			
MAX	Fijador	Magnum	Magnum

Fecha de Alta

09-01-2020

Versión

3 - 12/08/2024

STD	Magnum Diluido	Magnum
------------	----------------	--------

Drywall (gypsum plasterboard)

MAX	Magnum Diluido	Magnum	Magnum
------------	----------------	--------	--------

STD	Magnum Diluido	Magnum
------------	----------------	--------

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L