

502070

Fecha de Alta

03-08-2010

Versión

5 - 19/08/2024

CATALIZADOR ACRIPOL ESMALTE

MONTÓ
profesional

FAMILY

ESMALTES

LINE

POLIURETANOS MULTISOORTE

DESCRIPTION AND NATURE

Catalyst Acripol product range

USAGES

Indoors/Outdoors

PROPERTIES

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR ACRIPOL ESMALTE/IMPRIPO
Finish	.
Specific weight	0,95± 0,05 kg/l
Viscosity	11 +/- 2 SG
Solids in volume	36± 1
Solids in weight	40± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING

New surfaces

Restoring and maintenance

WAY OF USE

Application notes

shelf life of the mix 4h

Solvent for dilution and cleaning

Solvent 1410

Way of use

Aproximate dilution

SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

CATALIZADOR ACRIPOL ESMALTE

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.15 L, 0.8 L