

502172

Fecha de Alta

13-03-2009

Versión

8 - 18/04/2024

CATALIZADOR MONTOEPOX AQUA SUELOS

MONTÓ
profesional**FAMILY**
LINE

PAVIMENTOS

SUELOS INDUSTRIALES-PARKINGS

DESCRIPTION AND NATURE

Specific catalyst of the product Montoepon Aqua Grounds.

USAGESIndoors
Concrete
Ground**PROPERTIES****TECHNICAL CHARACTERISTICS**

Referencia Color	CATALIZADOR MONTOEPOX AQUA SUELOS
Mixture relation	5: 1
Specific weight	1,1 ± 0,05 kg/l
Solids in volume	100 ± 1
Solids in weight	100 ± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING**New surfaces****Restoring and maintenance****WAY OF USE****Application notes**

To mix perfectly with part A using machine for the mixed agitation and mix.

The product on this technical file has the indicated lifespan if it is stored in a dry place at a temperature between 5°C and 35°C in the original package.

The product can crystallise at low temperatures and, in that case, can be recovered by heating it at 50°C followed by stirring. In this way, it does not lose its characteristics and maintains its values and properties.

Solvent for dilution and cleaning

Water

Way of use**Aproximate dilution**

CATALIZADOR MONTOEPOX AQUA SUELOS

SYSTEM

Procedures depending of surface type

Primer**Intermedium****Finish**

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 Kg, 3 Kg