

502189

Fecha de Alta

15-03-2011

Versión

9 - 24/05/2024

CATALIZADOR IMPRIMACION EPOXI SUELOS

MONTÓ
profesional

FAMILY
LINE

PREPARACIONES, FONDOS E IMPR.

IMPRIMACIONES SUELOS

DESCRIPTION AND NATURE

Catalyst for Imprimación Epoxi Adherente 2 comp. water based.

USAGES

Outdoors/Indoors

PROPERTIES

To be used as catalyst product Imprimación Epoxi Adherente

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR IMPRIMACION EPOXI SUELOS
Finish	.
Specific weight	1,08± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING

New surfaces

Proceed according to data sheet Imprimación Epoxi Adherente + Catalyst

Restoring and maintenance

Proceed according to data sheet Imprimación Epoxi Adherente + Catalyst

WAY OF USE

Application notes

The product on this technical file has the indicated lifespan if it is stored in a dry place at a temperature between 5°C and 35°C in the original package.

The product can crystallise at low temperatures and, in that case, can be recovered by heating it at 50°C followed by stirring. In this way, it does not lose its characteristics and maintains its values and properties.

Solvent for dilution and cleaning

Way of use

Aproximate dilution

SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

CATALIZADOR IMPRIMACION EPOXI SUELOS

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Product of exclusive use for premises regulated under RD 117/2003 or 1999/13/CE regulations

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg, 4 Kg