

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024



FAMILY
LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS AL USO

DESCRIPTION AND NATURE

Extremely elastic waterproof putty. Specially formulated to treat cracks and fissures. Incorporates fibre materials which intensify its action.

USAGES

Outdoors/Indoors

Cement

Plaster

Repair of cracks, sealing of joints, filling of holes

PROPERTIES

Elasticity

Waterproof

Does not decrease

Complement for Tejamont

No cracking at all

Odourless when dry

Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT FIBRA ELASTICO
Finish	Matt
Specific weight	1,36± 0,05 kg/l
Solids in volume	53± 1
Solids in weight	68± 1
Minimum recommended thickness	1 mm
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR: 60%, 1mm): 4-8h
Dry to repaint	24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

-Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.

-Test suitability on surface.

-Wait till complete drying of product (30 days).

-Remove off any efflorescences and neutralize alkaline surfaces.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply product as recommended under Application Systems and Application points.

Restoring and maintenance

Remove off any remains or peeling of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Check adherence level and treat as per new surfaces.

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024

WAY OF USE

Application notes

- Use only recommended clean and dust-free tools as per Application Systems.
- Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Stainless trowel	al uso
Pallette / spatula	al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood/old outdoor			
MAX			
STD	Montopol fondo	Plasmont Elástico	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Old/New interior Wood			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Interior new/old buildings			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Outer old work painted badly state			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in fire. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in fire. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 36 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 2.5 L



FAMILY LINE

DESCRIPTION AND NATURE

Extremely elastic waterproof putty. Specially formulated to treat cracks and fissures. Incorporates fibre materials which intensify its action.

USAGES

PROPERTIES

Elasticity
Waterproof
Does not decrease
Complement for Tejamont
No cracking at all
Odourless when dry
Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight $1,36 \pm 0,05$ kg/lSolids in volume 53 ± 1 Solids in weight 68 ± 1

Minimum recommended thickness 1 mm

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%, 1mm): 4-8h

Dry to repaint 24-48h

Colours White

SURFACE PREPAIRING

New surfaces

Plaster and mortar cement:

-Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.

-Test suitability on surface.

-Wait till complete drying of product (30 days).

-Remove off any efflorescences and neutralize alkaline surfaces.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply product as recommended under Application Systems and Application points.

Restoring and maintenance

Remove off any remains or peeling of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024

Check adherence level and treat as per new surfaces.

WAY OF USE**Application notes**

-Use only recommended clean and dust-free tools as per Application Systems.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

al uso

al uso

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
New wood/old outdoor			
MAX			
STD	Montopol fondo	Plasmont Elástico	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Old/New interior Wood			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Interior new/old buildings			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
Outer old work painted badly state			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

502305


PLASMONT FIBRA ELASTICO

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024



PACKINGS

0.75 L, 2.5 L