

PLASMONT RENOVACION PLUS


FAMILY PREPARACIONES, FONDOS E IMPR.

LINE MASILLAS EN POLVO

DESCRIPTION AND NATURE

Powdered filler to smooth over textured surfaces. Holds on plastic paints. Excellent wet-on-wet adhesion. Can be applied in very thick coats.

USAGES

Indoors
Cement
Plaster
Plaster

PROPERTIES

Optimal applicability
No flammable
Fast drying
High thickness coats
It fix very good over Matt Water Paintings
Easy sandable
Good adhesion
Maximum recommended thickness per coat: 15 mm
Ideal for smoothing down dabbed and rough pitted finishes

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT RENOVACION PLUS
Finish	Matt
Specific weight	2,4± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR: 60%): 1-2h
Dry to repaint	(20°C HR: 60%): 12h
Colours	White

SURFACE PREPAIRING
New surfaces

Plaster and cement mortar:

- Test PLASMONT RENOVACION PLUS suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT RENOVACION PLUS as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

PLASMONT RENOVACION PLUS

Check adhesion and treat as on new funds.

WAY OF USE

Application notes

Use clean and rust-free tools detailed in the application system.

Anchor adequately.

We usually recommend coats of between 3-5 mm at most.

3 or more coats can be applied to a thickness of up to 15 mm.

The drying time indicated is a guideline only. It will depend on the surface conditions and the level of thickness applied.

Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coating, when the sandpaper does not clog, this indicates that the product is ready for repainting.

Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and Alta Decoración products.

- Do not apply the product at temperatures below 5° C, or to surfaces exposed to strong sunlight.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallete / spatula

Aproximate dilution

400-500 de agua por kg

400-500ml de agua por kg

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Fijador	Plasmont Renovación Plus	Familia 1, 2, 4, 11, y 12
STD	Plasmont Renovación Plus		Familia 1, 2, 4, 11, y 12
Asphalt fabric			
MAX	Plasmont Renovación Plus	Fijador	Familia 1, 2, 4, 11, y 12
STD	Plasmont Renovación Plus		Familia 1, 2, 4, 11, y 12
Plasterboard			
MAX	Plasmont Renovación Plus	Plasmont Renovación Plus	Familia 1, 2, 4, 11 y 12
STD	Plasmont Renovación Plus	Fijador	Familia 1, 2, 4, 11 y 12

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

15 Kg



FAMILY LINE

DESCRIPTION AND NATURE

Powdered filler to smooth over textured surfaces. Holds on plastic paints. Excellent wet-on-wet adhesion. Can be applied in very thick coats.

USAGES

PROPERTIES

Optimal applicability
No flammable
Fast drying
High thickness coats
It fix very good over Matt Water Paintings
Easy sandable
Good adhesion
Maximum recommended thickness per coat: 15 mm
Ideal for smoothing down dabbled and rough pitted finishes

TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	2,4± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 1-2h
Dry to repaint	(20°C HR: 60%): 12h
Colours	White

SURFACE PREPAIRING

New surfaces

Plaster and cement mortar:

PLASMONT RENOVACION PLUS

- Test PLASMONT RENOVACION PLUS suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT RENOVACION PLUS as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Check adhesion and treat as on new funds.

WAY OF USE

Application notes

Use clean and rust-free tools detailed in the application system.

Anchor adequately.

We usually recommend coats of between 3-5 mm at most.

3 or more coats can be applied to a thickness of up to 15 mm.

The drying time indicated is a guideline only. It will depend on the surface conditions and the level of thickness applied.

Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coating, when the sandpaper does not clog, this indicates that the product is ready for repainting.

Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatin and Alta Decoración products.

- Do not apply the product at temperatures below 5° C, or to surfaces exposed to strong sunlight.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

400-500 de agua por kg

400-500ml de agua por kg

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Fijador	Plasmont Renovación Plus	Familia 1, 2, 4, 11, y 12
STD	Plasmont Renovación Plus		Familia 1, 2, 4, 11, y 12
Asphalt fabric			
MAX	Plasmont Renovación Plus	Fijador	Familia 1, 2, 4, 11, y 12
STD	Plasmont Renovación Plus		Familia 1, 2, 4, 11, y 12
Plasterboard			
MAX	Plasmont Renovación Plus	Plasmont Renovación Plus	Familia 1, 2, 4, 11 y 12
STD	Plasmont Renovación Plus	Fijador	Familia 1, 2, 4, 11 y 12

SECURITY

502309


Fecha de Alta

28-11-2007

Versión

4 - 20/05/2024

PLASMONT RENOVACION PLUS



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

15 Kg