



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS EN POLVO

DESCRIPTION AND NATURE

Ultra-fine powdered filler for smoothing and making surfaces uniform before painting.

USAGES

Indoors
Cement
Plaster
Wood
Concrete
Plaster
Surface smoothing, final finish with filler putty

PROPERTIES

Adherence
Optimal applicability
No flammable
Fast drying
Minimum decrease
No need of sanding, but easy to do once dried
Long open time
Recommended thickness : 1 m

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT ACABADOS
Finish	Matt
Specific weight	2,53± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	1,6 m ² /L

Dry to touch	1-2h
Dry to repaint	12h
Colours	White

SURFACE PREPAIRING

New surfaces

- Cement / plaster mortar:
- Please check the suitability of the filler for the surface.
- Allow to set completely (at least 30 days).
- Remove possible efflorescence and neutralise alkaline surfaces.
- Sand excessively polished surfaces to increase porosity.
- Clean surface removing other products and/or residues.
- Back gouge any cracks or fissures down to repaired base, remove subsequent dust with brush and apply filler or plaster following the instructions provided in the Application and Application Systems.
- Never apply over the recommended coat thickness.
- On surfaces in an excessively poor condition suitable fixative should be used before applying filler (see product family 6): Fixative Emulsion, Fijamont, Fondo Montolite.

Fecha de Alta

08-08-2006

Versión

5 - 20/05/2024

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpæpering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

WAY OF USE**Application notes**

-Use clean and rust-free tools detailed in the Application System.

-Anchor adequately.

-Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.

-Suitable finishing products: Ovaldine, Montoplástica, Montonature, Montosintetic, Luxatín and High Decoration products.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallete / spatula

Aproximate dilution

añadir 400 ml de agua por kg de masillas

Añadir 400 ml de agua por kg de masilla

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Regular surface works			
MAX			
STD	Plasmont acabados	Fijador(Emulsión Fijadora, Fijamont)	Montoplástica, Montoneture, Ovaldine, Montosintetic, Luxatín, Alta decoració.
Irregular works			
MAX	Plasmont renovación		
STD	Plasmont acabados	Fijador(Emulsión Fijadora, Fijamont)	Montoplástica, Montoneture, Ovaldine, Montosintetic, Luxatín, Alta decoració.

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

Fecha de Alta

08-08-2006

Versión

5 - 20/05/2024

PACKINGS

1 Kg, 5 Kg, 15 Kg



FAMILY LINE

DESCRIPTION AND NATURE

Ultra-fine powdered filler for smoothing and making surfaces uniform before painting.

USAGES

PROPERTIES

Adherence
Optimal applicability
No flammable
Fast drying
Minimum decrease
No need of sanding, but easy to do once dried
Long open time
Recommended thickness : 1 m

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight 2,53± 0,05 kg/l

Solids in volume 100± 1

Solids in weight 100± 1

Aproximated performance by coat 1,6 m²/L

Dry to touch 1-2h

Dry to repaint 12h

Colours White

SURFACE PREPAIRING

New surfaces

- Cement / plaster mortar:
- Please check the suitability of the filler for the surface.
- Allow to set completely (at least 30 days).
- Remove possible efflorescence and neutralise alkaline surfaces.
- Sand excessively polished surfaces to increase porosity.
- Clean surface removing other products and/or residues.
- Back gouge any cracks or fissures down to repaired base, remove subsequent dust with brush and apply filler or plaster following the instructions provided in the Application and Application Systems.
- Never apply over the recommended coat thickness.
- On surfaces in an excessively poor condition suitable fixative should be used before applying filler (see product family 6): Fixative Emulsion, Fijamont, Fondo Montolite.

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpápering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

WAY OF USE**Application notes**

-Use clean and rust-free tools detailed in the Application System.

-Anchor adequately.

-Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.

-Suitable finishing products: Ovaldine, Montoplástica, Montonature, Montosintético, Luxatín and High Decoration products.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

añadir 400 ml de agua por kg de masillas

Añadir 400 ml de agua por kg de masilla

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Regular surface works			
MAX			
STD	Plasmont acabados	Fijador(Emulsión Fijadora, Fijamont)	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.
Irregular works			
MAX			
STD	Plasmont renovación	Fijador(Emulsión Fijadora, Fijamont)	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

502315


PLASMONT ACABADOS

Fecha de Alta

08-08-2006

Versión

5 - 20/05/2024



PACKINGS

1 Kg, 5 Kg, 15 Kg