



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS AL USO

DESCRIPTION AND NATURE

Ready to use putty, for filling tiles and ceramics, with good adhesion on non-porous or slightly porous surfaces.

USAGES

Outdoors/Indoors

Cement

Plaster

Brick

Tiles

Ceramic material

PROPERTIES

Strongness

Penetration power

Does not decrease

Re-finishable with any putty from the family Plasmont

Without product loosings, remainings can be used immediately

Able to be sanded

Good adhesion

Drying fast

No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT AL USO AZULEJOS
Finish	Matt
Specific weight	1,78± 0,05 kg/l
Solids in volume	68± 1
Solids in weight	84± 1
Minimum recommended thickness	1000 micras máximo
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR: 60%): 1-3h
Dry to repaint	(20°C HR: 60%): 24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

For filling and eliminating cracks and fissures on cement/plaster mortars.

- Check the suitability of the filler for the base.
- Wait until fully hardened (at least 30 days).
- Clean possible efflorescence from the base and neutralise alkaline surfaces.
- Sand down highly polished surfaces to open up the pore.
- Remove any foreign products and residues from the base.
- Open up any cracks and fissures to repair the base, remove the dust produced with a brush and apply the filler or plaster as indicated in the Application Systems and Application sections.
- Never exceed the maximum recommended layer thickness.
- Fix very crumbly surfaces with a suitable fixative before filling (see Family 6): Emulsión Fijadora or Fijamont.

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024

For tiles, brickwork, ceramic material and on non-porous or slightly porous plaster work: Remove any foreign products from the base and apply directly.

Restoring and maintenance

Clean the base to remove any foreign or loose products or materials in poor condition. Sand down the base or use other mechanical means to open the pore if it is closed. Check adhesion and proceed as with new bases.

WAY OF USE

Application notes

- Use the tools indicated under application methods, clean and free of rust.
- Repaint once the indicated time has passed. As this depends on the moisture levels, temperature and thickness of the layer, if the sandpaper does not stick this will tell us that the product is ready to proceed.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Stainless trowel	Uso
Pallette / spatula	Uso
Pallette	Uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Emulsión Fijadora, Fijamont	Plasmont Azulejos	Repintado con cualquier tipo de pintura
STD	Emulsión Fijadora	Plasmont Azulejos	Repintado con cualquier tipo de pintura
Tiles, Ceramic Material			
MAX	Plasmont al Uso Azulejos	Plasmont Renovación, Alisar, Standar	Repintado con cualquier tipo de pintura
STD	Plasmont al Uso Azulejos		Repintado con cualquier tipo de pintura
Brickwork			
MAX	Plasmont al Uso Azulejos	Plasmont Renovación, Alisar, Standar	Repintado con cualquier tipo de pintura
STD	Plasmont al Uso Azulejos		Repintado con cualquier tipo de pintura

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

5 Kg, 20 Kg

**FAMILY
LINE****DESCRIPTION AND NATURE**

Ready to use putty, for filling tiles and ceramics, with good adhesion on non-porous or slightly porous surfaces.

USAGES**PROPERTIES**

Strongness
Penetration power
Does not decrease
Re-finishable with any putty from the family Plasmont
Without product loosings, remainings can be used immediately
Able to be sanded
Good adhesion
Drying fast
No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	1,78± 0,05 kg/l
Solids in volume	68± 1
Solids in weight	84± 1
Minimum recommended thickness	1000 micras máximo
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 1-3h
Dry to repaint	(20°C HR: 60%): 24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

For filling and eliminating cracks and fissures on cement/plaster mortars.

- Check the suitability of the filler for the base.
- Wait until fully hardened (at least 30 days).
- Clean possible efflorescence from the base and neutralise alkaline surfaces.
- Sand down highly polished surfaces to open up the pore.
- Remove any foreign products and residues from the base.
- Open up any cracks and fissures to repair the base, remove the dust produced with a brush and apply the filler or plaster as indicated in the Application Systems and Application sections.
- Never exceed the maximum recommended layer thickness.
- Fix very crumbly surfaces with a suitable fixative before filling (see Family 6): Emulsión Fijadora or Fijamont.

For tiles, brickwork, ceramic material and on non-porous or slightly porous plaster work: Remove any foreign products from the base and apply directly.

Restoring and maintenance

Clean the base to remove any foreign or loose products or materials in poor condition. Sand down the base or use other mechanical means to open the pore if it is closed. Check adhesion and proceed as with new bases.

WAY OF USE**Application notes**

- Use the tools indicated under application methods, clean and free of rust.
- Repaint once the indicated time has passed. As this depends on the moisture levels, temperature and thickness of the layer, if the sandpaper does not stick this will tell us that the product is ready to proceed.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Stainless trowel	Uso
Pallette / spatula	Uso
Pallette	Uso

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
New work			
MAX	Emulsión Fijadora, Fijamont	Plasmont Azulejos	Repintado con cualquier tipo de pintura
STD	Emulsión Fijadora	Plasmont Azulejos	Repintado con cualquier tipo de pintura
Tiles, Ceramic Material			
MAX	Plasmont al Uso Azulejos	Plasmont Renovación, Alisar, Standar	Repintado con cualquier tipo de pintura
STD	Plasmont al Uso Azulejos		Repintado con cualquier tipo de pintura
Brickwork			
MAX	Plasmont al Uso Azulejos	Plasmont Renovación, Alisar, Standar	Repintado con cualquier tipo de pintura
STD	Plasmont al Uso Azulejos		Repintado con cualquier tipo de pintura

SECURITY

Fecha de Alta

04-07-2007

Versión

5 - 21/05/2024

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE**PACKINGS**

5 Kg, 20 Kg