



## FAMILY LINE

PREPARACIONES, FONDOS E IMPR.  
MASILLAS AL USO

## DESCRIPTION AND NATURE

Plastic putty in paste form. Ready to use. Outstanding application, whiteness .

## USAGES

Outdoors/Indoors

Cement

Plaster

Wood

Concrete

Plaster

It can be used for filling and levelling surface imperfections, it helps crack filling and seal off joints

## PROPERTIES

Strongness

No flammable

Penetration power

Without product loosings, remainings can be used immediately

It avoids losing time for mixing, because product is ready to use

Minimum decrease

Good adhesion

Recommended thickness per coat : 1,5 mm

Drying fast

Good applicability

## TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT AL USO MULTIUSO
------------------	--------------------------

Finish	Matt
--------	------

Specific weight	1,82± 0,05 kg/l
-----------------	-----------------

Solids in volume	59± 1
------------------	-------

Solids in weight	79± 1
------------------	-------

Aproximated performance by coat	Depending of product usage
---------------------------------	----------------------------

Dry to touch	(20°C HR: 60%): 1-3h
--------------	----------------------

Dry to repaint	24h
----------------	-----

Colours	White
---------	-------

## SURFACE PREPAIRING

### New surfaces

Plaster and cement mortar:

-Apply suitable fixer before puttying (see family 6) Emulsion Fijadora, Fijamont, Fijalite.

-Test PLASMONT AL USO suitability on surface.

-Wait till complete drying of product (30 days).

-Remove off any efflorescences and neutralize alkaline surfaces.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT AL USO as recommended under Application Systems and Application points.

-For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.

Fecha de Alta

15-07-2008

Versión

4 - 21/05/2024

-Recommended maximum thickness per coat should always be observed.

Wood:

-Test PLASMONT ACABADOS suitability on surface.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT ACABADOS as recommended under Application Systems and Application points.

-Recommended maximum thickness per coat should always be observed.

-Only apply on wood in good condition, with no trace of resine exudates, dry and free of dust and grease, with less than 20% moisture level.

-Old wood should be previously sandpapered and dust-free.

### Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

## WAY OF USE

### Application notes

-Very absorbent surfaces should be previously moistened.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

-Use only recommended clean and dust-free tools as per Application Systems.

### Solvent for dilution and cleaning

Water

#### Way of use                      Approximate dilution

Stainless trowel                      uso

Pallette / spatula                      uso

Pallette                      uso

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al Uso	Fijador(Emulsión Fijadora Fijamont)	Montoplástica, Ovaldine, Montonature, Montosintético, Luxatín
<b>Indoor wood</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al uso	Fondos e imprimaciones para madera (familia 4)	Ovaldine, Montonature, montosintético, Luxatín, Acabados pigmentados para madera

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

15-07-2008

Versión

4 - 21/05/2024

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.5 Kg, 1 Kg, 5 Kg, 20 Kg

**FAMILY  
LINE****DESCRIPTION AND NATURE**

Plastic putty in paste form. Ready to use. Outstanding application, whiteness .

**USAGES****PROPERTIES**

Strongness  
No flammable  
Penetration power  
Without product loosings, remainings can be used immediately  
It avoids losing time for mixing, because product is ready to use  
Minimum decrease  
Good adhesion  
Recommended thickness per coat : 1,5 mm  
Drying fast  
Good applicability

**TECHNICAL CHARACTERISTICS**

Referencia Color	
Finish	Matt
Specific weight	1,82± 0,05 kg/l
Solids in volume	59± 1
Solids in weight	79± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 1-3h
Dry to repaint	24h
Colours	White

**SURFACE PREPAIRING****New surfaces**

Plaster and cement mortar:

Fecha de Alta

15-07-2008

Versión

4 - 21/05/2024

- Apply suitable fixer before puttying (see family 6) Emulsion Fijadora, Fijamont, Fijalite.
- Test PLASMONT AL USO suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT AL USO as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Wood:

- Test PLASMONT ACABADOS suitability on surface.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT ACABADOS as recommended under Application Systems and Application points.
- Recommended maximum thickness per coat should always be observed.
- Only apply on wood in good condition, with no trace of resine exudates, dry and free of dust and grease, with less than 20% moisture level.
- Old wood should be previously sandpapered and dust-free.

### Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

## WAY OF USE

### Application notes

- Very absorbent surfaces should be previously moistened.
- Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.
- Use only recommended clean and dust-free tools as per Application Systems.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Stainless trowel	uso
Pallette / spatula	uso
Pallette	uso

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al Uso	Fijador(Emulsión Fijadora Fijamont)	Montoplástica, Ovaldine, Montonature, Montosintético, Luxatín
<b>Indoor wood</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al uso	Fondos e imprimaciones para madera (familia 4)	Ovaldine, Montonature, montosintético, Luxatín, Acabados pigmentados para madera

## SECURITY

Fecha de Alta

15-07-2008

Versión

4 - 21/05/2024

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE****PACKINGS**

0.5 Kg, 1 Kg, 5 Kg, 20 Kg