

Fecha de Alta

04-07-2007

Versión

3 - 21/05/2024



FAMILY PREPARACIONES, FONDOS E IMPR.

LINE MASILLAS MADERA

DESCRIPTION AND NATURE

Standard putty in a range of colours for restoring, repairing and moulding wood before painting.

USAGES

Indoors

Wood after varnished

Restoring furniture, frames, crack filler, defects

PROPERTIES

Does not decrease
Covers imperfections
Base putty
Fast sanding
Good adhesion
No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color PLASMONT MADERA NATURAL

Finish Matt

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%, 1mm): 5-10min

Dry to repaint (20°C HR: 60%, 1mm): 1-2h

Colours Natural, Pino, Haya, Roble, Nogal, Teka, Sapeli, Caoba

SURFACE PREPAIRING

New surfaces

- Wood:
- Remove external products and/or residues from the wood.
- Apply to clean and dry wood.
- Back gouge cracks or fissures back to repaired base and remove the dust.
- Apply as instructed in the Application Systems and Application.

Restoring and maintenance

- Varnished and lacquered wood:
- Remove old paint with paint stripper or other means until healthy wood is uncovered.
- Proceed as you would for a new surface

WAY OF USE

Application notes

Apply several coats, at least two, using a spatula. Allow to dry between coats. Apply the final coat generously and leave to dry for 1 to 2 hours before sanding. Allow to dry completely before varnishing or painting. Paint or varnish with Selladora Sellalux, synthetic enamels and synthetic varnishes, Montolac products or Montopol products, following the instructions provided in their technical specifications.

Solvent for dilution and cleaning

Solvent 1407

Fecha de Alta

04-07-2007

Versión

3 - 21/05/2024

Way of use

Palletes / spatula

Aproximate dilution

0

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto
STD	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS


0.12 Kg

**FAMILY
LINE****DESCRIPTION AND NATURE**

Standard putty in a range of colours for restoring, repairing and moulding wood before painting.

USAGES**PROPERTIES**

Does not decrease
Covers imperfections
Base putty
Fast sanding
Good adhesion



No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%, 1mm): 5-10min

Dry to repaint (20°C HR: 60%, 1mm): 1-2h

Colours Natural, Pino, Haya, Roble, Nogal, Teka, Sapeli, Caoba

SURFACE PREPAIRING

New surfaces

- Wood:
- Remove external products and/or residues from the wood.
- Apply to clean and dry wood.
- Back gouge cracks or fissures back to repaired base and remove the dust.
- Apply as instructed in the Application Systems and Application.

Restoring and maintenance

- Varnished and lacquered wood:
- Remove old paint with paint stripper or other means until healthy wood is uncovered.
- Proceed as you would for a new surface

WAY OF USE

Application notes

Apply several coats, at least two, using a spatula. Allow to dry between coats. Apply the final coat generously and leave to dry for 1 to 2 hours before sanding. Allow to dry completely before varnishing or painting. Paint or varnish with Selladora Sellalux, synthetic enamels and synthetic varnishes, Montolac products or Montopol products, following the instructions provided in their technical specifications.

Solvent for dilution and cleaning

Solvent 1407

Way of use Aproximate dilution

Pallette / spatula

0

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto
STD	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

502326


PLASMONT MADERA

Fecha de Alta

04-07-2007

Versión

3 - 21/05/2024



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.12 Kg