



FAMILY LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS HIERRO Y METALES

DESCRIPTION AND NATURE

Two-component bodybuilder type polyester paste putty with excellent anchorage on iron and metals and other materials. With high filling power designed to cover defects and level surfaces before painting.

USAGES

Outdoors/Indoors

Iron

Galvanized iron

Polyester

Cement mortars

PROPERTIES

Elasticity

Levelling

Thixotropic

Fast drying

Base putty

Fast sanding

High filling power, given its high solids content.

Good adhesion

Easy to sand

Drying fast

No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT METALES CREMA
Mixture relation	100 partes (masilla): 2-2.5 (Catalizador Masilla)
Finish	Matt
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR: 60%): 5-10min
Dry to repaint	(20°C HR: 60%): 30min
Colours	Putty

SURFACE PREPAIRING

New surfaces

- To clean all the strange product support and/or remainders.
- To apply on clean, dry, sandpaperings and taken the grease out of bottoms.
- To open to possible outcries or fissures until adjusted bottom and to eliminate remainders and produced dust.
- To apply so and as indicates in the sections Application.

Restoring and maintenance

- To eliminate old paintings by means of pickling or any other procedure, until healthy bottom.
- To come as in new supports.

Fecha de Alta

06-03-2008

Versión

6 - 21/05/2024

WAY OF USE

Application notes

To mix both components in the suitable proportion. To mix only the amount to use during the time of life of the mixture.

To apply the product with a spatula.

You let dry.

To sandpaper in dry with grain sandpaper P-80 or P-240. Once sandpapering to come the painted one with the chosen painting.

T^a < 5 ° C polyester putties harden not

Solvent for dilution and cleaning

Solvent 1406

Way of use

Pallette / spatula

Aproximate dilution

0

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX	Plasmont Metales	Imprimación Pintura de Acabado	Acropol, Montoepox
STD	Plasmont Metales	Imprimación Pintura de Acabado	Montosintétic, Luxatín
Metal decoration			
MAX	Plasmont metales	Imprimación Pintura Acabado	Acropol, Montoepox
STD	Plasmont metales	Imprimación Pintura Acabado	Montosintétic, Luxatín
Plastic			
MAX	Plasmont metales	Imprimación Pintura de Acabado	Acropol, Montoepox
STD	Plasmont metales	Imprimación Pintura de Acabado	Montosintétic, Luxatín

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg



FAMILY LINE

DESCRIPTION AND NATURE

Two-component bodybuilder type polyester paste putty with excellent anchorage on iron and metals and other materials. With high filling power designed to cover defects and level surfaces before painting.

USAGES

PROPERTIES

Elasticity
 Levelling
 Thixotropic
 Fast drying
 Base putty
 Fast sanding
 High filling power, given its high solids content.
 Good adhesion
 Easy to sand
 Drying fast
 No cracking at all

TECHNICAL CHARACTERISTICS

Referencia Color

Mixture relation 100 partes (masilla): 2-2.5 (Catalizador Masilla)

Finish Matt

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%): 5-10min

Dry to repaint (20°C HR: 60%): 30min

Colours Putty

SURFACE PREPAIRING

New surfaces

- To clean all the strange product support and/or remainders.
- To apply on clean, dry, sandpaperings and taken the grease out of bottoms.
- To open to possible outcries or fissures until adjusted bottom and to eliminate remainders and produced dust.
- To apply so and as indicates in the sections Application.

Restoring and maintenance

- To eliminate old paintings by means of pickling or any other procedure, until healthy bottom.
- To come as in new supports.

WAY OF USE

Application notes

To mix both components in the suitable proportion. To mix only the amount to use during the time of life of the mixture.

To apply the product with a spatula.

You let dry.

To sandpaper in dry with grain sandpaper P-80 or P-240. Once sandpapering to come the painted one with the chosen painting.

T^a < 5 ° C polyester putties harden not

Solvent for dilution and cleaning

Solvent 1406

Way of use

Pallette / spatula

Aproximate dilution

0

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX	Plasmont Metales	Imprimación Pintura de Acabado	Acropol, Montoepox
STD	Plasmont Metales	Imprimación Pintura de Acabado	Montosintétic, Luxatín
Metal decoration			
MAX	Plasmont metales	Imprimación Pintura Acabado	Acropol, Montoepox
STD	Plasmont metales	Imprimación Pintura Acabado	Montosintétic, Luxatín
Plastic			
MAX	Plasmont metales	Imprimación Pintura de Acabado	Acropol, Montoepox
STD	Plasmont metales	Imprimación Pintura de Acabado	Montosintétic, Luxatín

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

1 Kg