

PLASMONT AL USO REPARACION FACHADAS



FAMILY
LINE

PREPARACIONES, FONDOS E IMPR.
MASILLAS AL USO

DESCRIPTION AND NATURE

Standard cement-free putty for outdoor use, particularly suitable for repair jobs where quick repainting is required. Does not produce saltpetre or stains on the coating. Finish like cement mortar.

USAGES

Outdoors/Indoors
Cement
Plaster
Concrete
Supports with porosity

PROPERTIES

Strongness
Elasticity
No flammable
Adequate for High thickness coats
It avoids losing time for mixing, because product is ready to use
Anti-saltpetre
Good applicability
Do not cause saltpetre spots after painting
Not alcalyne
Do not cause white spots, the usual ones on cement surfaces not hardened or with saltpetre
Quick repainting because must not wait to hardness, like in the cement based products
Minimum decrease
Good adhesion

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT AL USO REPARACION FACHADAS
Finish	Slightly textured
Specific weight	1,87 ± 0,05 kg/l
Solids in volume	70 ± 1
Solids in weight	85 ± 1

Aproximated performance by coat Depending of product usage

Dry to touch	(20°C HR: 60%): 12-24h
Dry to repaint	(20°C HR: 60%): 24-48h
Colours	7032 grey

SURFACE PREPAIRING

New surfaces

Cement mortar, plaster or porous brickwork:

- Check the suitability of the putty for the base.
- Wait until the base is completely set.
- Clean possible efflorescence from the base and neutralise alkaline surfaces.
- Sand down highly polished surfaces to open up the pore.
- Remove any foreign products and residues from the base.
- Open up any cracks and fissures until the base is repaired, remove the dust produced with a brush and apply the putty or plaster as indicated in the Application Systems and Application sections.

PLASMONT AL USO REPARACION FACHADAS

- Never exceed the maximum recommended layer thickness.

Restoring and maintenance

- Clean the base to remove any foreign or loose products or materials in bad condition.
- Sand down the base or use other mechanical means to open the pore if it is closed.
- Check the adhesion and treat as a new base.

WAY OF USE

Application notes

- Once the base has been prepared, dampen it with water and apply immediately.
- Important: To ensure an even appearance, shortly before the base is dry to touch, wipe with a damp sponge using the typical swirling technique.
- Use the tools indicated under application methods, clean and free of rust.
- Repaint once the indicated time has passed. As this depends on moisture levels, temperature and thickness of the layer, touch will tell us that the product is ready to proceed.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Aproximate dilution

Uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX		PLasmont al Uso Reparación fachadas	Repintable con cualquier pintura
STD		PLasmont al Uso Reparación fachadas	Repintable con cualquier pintura
Asphalt fabric			
MAX	abrir poro lijando si procede	PLasmont al Uso Reparación fachadas	Repintable con cualquier pintura
STD	abrir poro lijando si procede	PLasmont al Uso Reparación fachadas	Repintable con cualquier pintura

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

5 Kg, 20 Kg