

Fecha de Alta

23-04-2008

Versión

14 - 21/08/2024



FAMILY
LINE

REVESTIMIENTOS DE FACHADAS
LISOS

DESCRIPTION AND NATURE

Smooth coating for protection and decoration of façades and exterior walls. Especially suitable on fragile and problematic bases such as whitewash or tempera. Provides good adhesion and water repellence.

USAGES

Outdoors/Indoors

Weak supports

Lime Mortars

Old, "estolite" and saltpetre whitewashed façades

Protection of surfaces with adhesion problems

PROPERTIES

Opacity: Class 1 for a performance of 6 m²/litre (according to Standard UNE-EN 13300)

Water vapor permeability: V1 (maximum breathable) (according to UNE-EN 1062-1 standard)

Gloss level: matt (according to 13300 standard, at 85° reflectance <10)

Washability: Class 4 (according to UNE-EN 13300 Standard)

Permeability to liquid water: W1 (maximum impermeability) (according to UNE-EN 1062-1 standard)

Gloss: G3 (matt, according to the UNE-EN 1062-1 standard)

Dry film thickness: E3 (between 100 and 200 microns, according to the UNE-EN 1062-1 standard) calculated for a yield of 3 m² / l in two coats for the white. This information may vary depending on the color chosen.

TECHNICAL CHARACTERISTICS

Referencia Color NEVADA SILFLEX BLANCO

Finish Smooth matt

Specific weight 1,51 ± 0,05 kg/l

Viscosity 104 +/- 20 PO

Solids in volume 40 ± 1

Solids in weight 62 ± 1

VOC Cat. c/BA 75/40 (2007/2010): 2,76 g/l

Aproximated performance by coat 4-8 m²/L

Dry to touch (20°C HR: 60%): 1h

Dry to repaint (20°C HR: 60%): 4-6h

Colours White 103 and colours from the Nevada Fachadas chart.

SURFACE PREPAIRING

New surfaces

Restoring and maintenance

Product can be applied over whitewash:

1. Fully remove any old paint that is loose or in bad condition.
2. Dull down glossy surfaces to ensure good adhesion.
3. On painted bases, check the solidity and adhesion of the paint and the type of paint to avoid potential incompatibilities and remove dust and dirt before repainting.
4. Use plaster to fill any defects in the base (In family 6 see PREPARING BASES lines corresponding to powder plaster and prepared fillers to select a suitable solution).
5. Treat mouldy bases with Monto Limpia Moho.

Fecha de Alta

23-04-2008

Versión

14 - 21/08/2024

WAY OF USE

Application notes

- Do not apply the product at temperatures below 5°C C or above 35°C or with imminent risk of rain.
- Do not apply in full sun or on excessively humid days.
- Shake the product until it is perfectly homogenised.
- For the first coat, dilute the product according to the porosity and state of the surface.
- Finish with one or more lightly diluted coats until the surface is completely covered.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low pressure turbo	10-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX	Nevada Silflex diluido	Nevada Silflex	Nevada Silflex
STD	Nevada Silflex diluido		Nevada Silflex
Old paintings of lime			
MAX	Nevada Silflex diluido	Nevada Silflex	Nevada Silflex
STD	Nevada Silflex diluido		Nevada Silflex

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L