

Fecha de Alta

01-08-2006

Versión

3 - 21/08/2024



FAMILY
LINE

PRODUCTOS PARA USO ESPECIFICO
ADITIVOS

DESCRIPTION AND NATURE

Matting additive to be added to solvent based products.

USAGES

Universal flatting for solvent-based systems

PROPERTIES

Does not alter product properties to which is added
Additable over enamels, synthetic varnishes, Nitrocellulosic, Poliuretanic
Allows the adjustment of desired gloss

TECHNICAL CHARACTERISTICS

Referencia Color	CONVERPLUS MATIZADOR
Mixture relation	Se recomienda aditivar del 5 al 20% de converplus
Finish	Transparent
Specific weight	1,08± 0,05 kg/l
Solids in volume	27± 1
Solids in weight	43± 1
Aproximated performance by coat	Depending of product usage
Colours	Transparent

SURFACE PREPAIRING

New surfaces

As per product to be added to.

Restoring and maintenance

As per product to be added to.

WAY OF USE

Application notes

- Stir product until perfectly homogenized.
- Mix up with product base by spatula or agitator.
- Addition: 5-20% in volume.
- Apply recommended primer for every product.
- Always follow the recommended application systems indicated in corresponding product data sheet.

Solvent for dilution and cleaning

Solvent 1405

Way of use

Aproximate dilution

Fecha de Alta

01-08-2006

Versión

3 - 21/08/2024

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
On usualy surfaces			
MAX			
STD	Idem productos Monto a aditivar	Idem productos Monto a aditivar	Idem productos Monto a aditivar+Converplus matizador

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L