

AGUARRAS SIMIL PREMIUM 1417


FAMILY DISOLVENTES

LINE DISOLVENTES

DESCRIPTION AND NATURE

Solvent of aliphatic hydrocarbons combined with turpentine and terpenes.

USAGES

Regulation and control of the viscosity of application in the paintings where his use is recommended
Excellent thinner for enamels and synthetic varnishes, as well as products where its use as a solvent is specified, for application with brush or roller.
Cleanliness of tools in the recommended products

PROPERTIES

Optimal applicability
Characteristic smell
Suitable evaporation velocity, obtaining a perfect balance between external and internal drying
Delays product initial drying time, but not the final, for which permits an excellent leveling
Does not harms final product properties if the proportions are the adecuaded

TECHNICAL CHARACTERISTICS

Referencia Color	AGUARRAS SIMIL PREMIUM 1417
Finish	Transparent
Specific weight	0,76± 0,05 kg/l
Solids in volume	0± 1
Solids in weight	0± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING
New surfaces

Proceed following the paint instructions in which this product is recommended.

Restoring and maintenance

Proceed following the paint instructions in which this product is recommended.

WAY OF USE
Application notes

- As a viscosity regulator:
- Add on top of paint or varnish, in the proportion stated in the specifications sheet of the product to be diluted.
- Slowly stir the previous mix with a spatula until you get a smooth mixture.
- As a tool cleaning solvent:
- Clean tools immediately after use until all varnish and paint has completely disappeared.
- Then wash with soapy water and dry immediately after washing.

Solvent for dilution and cleaning

AGUARRAS SIMIL PREMIUM 1417

Way of use**Aproximate dilution****SYSTEM****Procedures depending of surface type****Primer****Intermedium****Finish****SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.25 L, 0.5 L, 1 L