

Fecha de Alta

10-10-2007

Versión

4 - 30/05/2024

**FAMILY****DISOLVENTES****LINE****DISOLVENTES****DESCRIPTION AND NATURE**

Solvent of aliphatic hydrocarbons and terpenes.

**USAGES**

Regulation and control of the viscosity of application in the paintings where his use is recommended

Cleanliness of tools in the recommended products

Turpentine substitute

**PROPERTIES**

Optimal applicability

Suitable evaporation velocity, obtaining a perfect balance between external and internal drying

Delays product initial drying time, but not the final, for which permits an excellent leveling

Does not harms final product properties if the proportions are the adecuated

Obtained from the distillation of terpenes, hydrocarbons and derivatives

**TECHNICAL CHARACTERISTICS**

Referencia Color	AGUARRAS SIMIL 1413
Finish	Transparent
Specific weight	0,75± 0,05 kg/l
Solids in volume	0± 1
Solids in weight	0± 1
Aproximated performance by coat	Depending of product usage

Colours

-

**SURFACE PREPAIRING****New surfaces**

Proceed following the paint instructions in which this product is recommended.

**Restoring and maintenance**

Proceed following the paint instructions in which this product is recommended.

**WAY OF USE****Application notes**

-As a viscosity regulator:

-Add on top of paint or varnish, in the proportion stated in the specifications sheet of the product to be diluted.

-Slowly stir the previous mix with a spatula until you get a smooth mixture.

-As a tool cleaning solvent:

-Clean tools immediately after use until all varnish and paint has completely disappeared.

-Then wash with soapy water and dry immediately after washing.

**Solvent for dilution and cleaning**

Fecha de Alta

10-10-2007

Versión

4 - 30/05/2024

Way of use

Aproximate dilution

**SYSTEM**

Procedures depending of surface type

Primer

Intermedium

Finish

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.5 L, 1 L, 5 L