

# DISOLVENTE UNIVERSAL 1405



**FAMILY** DISOLVENTES  
**LINE** DISOLVENTES

## DESCRIPTION AND NATURE

Solvent mix which, as its name implies, is suitable to cleaning the majority of solvent-based paints.

## USAGES

Regulation and control of the viscosity of application in the paintings where his use is recommended

Cleanliness of tools in the recommended products

Primers

Quick drying synthetic enamels

Chlorinated rubber paints

Nitrocellulose lacquers pigmented and transparent

Specific for application with spray gun

## PROPERTIES

Suitable evaporation velocity, obtaining a perfect balance between external and internal drying

Does not harms final product properties if the proportions are the adecuated

Great dilution capability

Its evaporation quickness makes products in which are used to dry more quickly as solvent for sinthetics and grease-1401

## TECHNICAL CHARACTERISTICS

Referencia Color DISOLVENTE UNIVERSAL 1405

Specific weight 0,83± 0,05 kg/l

Solids in volume 0± 1

Solids in weight 0± 1

Aproximated performance by coat Depending of product usage

Dry to touch Medium

Colours Transparent

## SURFACE PREPAIRING

### New surfaces

Proceed as indicated on the paint on which this product is recommended.

### Restoring and maintenance

Proceed as indicated on the paint on which this product is recommended.

## WAY OF USE

### Application notes

-As a viscosity regulator:

-Add to paint or varnish, in the proportion set out in the specifications of the product to be diluted.

-Stir the above mixture slowly with a spatula until perfectly blended.

-Only products manufactured by Monto and which are specifically recommended are indicated in the application box.

-As a solvent for cleaning tools:

-Clean the tools immediately after use, until the varnish or paint has completely disappeared.

-Then clean with soapy water and dry immediately after washing.

# DISOLVENTE UNIVERSAL 1405

## Solvent for dilution and cleaning

Way of use

Aproximate dilution

## SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.25 L, 0.5 L, 0.75 L, 1 L, 5 L, 25 L, 200 L, 1000 L