#### 503450

Fecha de Alta 30-06-2006 Versión

# **DISOLVENTE LIMPIEZA 1406**



6 - 23/08/2024



FAMILY DISOLVENTES
LINE DISOLVENTES

# **DESCRIPTION AND NATURE**

Mixture of solvents, like his name indicates, it is suitable for the cleanliness of most of the solvent based paints

## **USAGES**

Cleanliness of tools in the recommended products

#### **PROPERTIES**

High power of cleanliness

High compatibility with the majority of products solvent base

TECHNICAL CHARACTERISTCS	
Referencia Color	DISOLVENTE LIMPIEZA 1406
Specific weight	0,81± 0,05 kg/l
Solids in volume	0± 1
Solids in weight	0± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	Median
Colours	Transparent

# SURFACE PREPAIRING

#### **New surfaces**

Proceed following the paint instructions in which this product is recommended.

# Restoring and maintenance

Proceed following the paint instructions in which this product is recommended.

# **WAY OF USE**

#### **Application notes**

- -As a viscosity regulator:
- -Add on top of paint or varnish, in the proportion stated in the specifications sheet of the product to be diluted.
- -Slowly stir the previous mix with a spatula until you get a smooth mixture.
- -As a tool cleaning solvent:
- -Clean tools immediately after use until all varnish and paint has completely disappeared.
- -Then wash with soapy water and dry immediately after washing.

## Solvent for dilution and cleaning

Way of use Aproximate dilution

#### 503450

# **DISOLVENTE LIMPIEZA 1406**



Fecha de Alta 30-06-2006 Versión

6 - 23/08/2024

## SYSTEM

Procedures depending of surface type

Primer Intermedium Finish

#### **SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

#### NOTE

Maximum recommended storage time: 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between  $5^{\circ}$  and  $35^{\circ}$ C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

5 L, 25 L, 200 L, 1000 L