

Fecha de Alta

10-10-2007

Versión

3 - 30/05/2024

**FAMILY** DISOLVENTES  
**LINE** DISOLVENTES**DESCRIPTION AND NATURE**

Solvent specially designed to regulate the viscosity and cleaning tools epoxy, solvent-based paints.

**USAGES**

Regulation and control of the viscosity of application in the paintings where his use is recommended  
Cleanliness of tools in the recommended products

**PROPERTIES**

Characteristic smell  
Suitable evaporation velocity, obtaining a perfect balance between external and internal drying  
Does not harms final product properties if the proportions are the adecuated  
Great dilution capability

**TECHNICAL CHARACTERISTICS**

|                                 |                            |
|---------------------------------|----------------------------|
| Referencia Color                | DISOLVENTE EPOXI 1411      |
| Finish                          | Transparent                |
| Specific weight                 | 0,82± 0,05 kg/l            |
| Solids in volume                | 0± 1                       |
| Solids in weight                | 0± 1                       |
| Aproximated performance by coat | Depending of product usage |

**SURFACE PREPAIRING****New surfaces**

Proceed following the paint instructions in which this product is recommended.

**Restoring and maintenance**

Proceed following the paint instructions in which this product is recommended.

**WAY OF USE****Application notes**

- As a viscosity regulator:
- Add on top of part pigmented, in the proportion stated in the specifications sheet of the product to be diluted.
- Slowly stir the previous mix with a spatula until you get a smooth mixture.
- As a tool cleaning solvent:
- Clean tools immediately after use until all varnish and paint has completely disappeared.
- Then wash with soapy water and dry immediately after washing.

Solvent for**Solvent for dilution and cleaning****Way of use****Aproximate dilution**

Fecha de Alta

10-10-2007

Versión

3 - 30/05/2024

**SYSTEM****Procedures depending of surface type**

Primer

Intermedium

Finish

**Generic solvent product and cleaning of tools****MAX****STD** Impriepox M-10+Cat.Montoepon M-10/Montoepon  
S-10+Cat.**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

1 L, 5 L, 25 L