

Fecha de Alta

17-01-2011

Versión

8 - 23/08/2024

**FAMILY**
LINE

PRODUCTOS PARA USO ESPECIFICO

QUITAPINTURAS

DESCRIPTION AND NATURE

Semi-gel fast-acting stripper. For stripping all types of paint from any surface. Biodegradable, non-toxic. Methylene chloride free.

USAGES

Outdoors/Indoors

Metal

Wood,

PROPERTIES

Optimal applicability

Open time

It removes easily the paintings , by contact and some scrapping

do not enerates dust

Eliminates paints and varnishes

Does not harms wood

Does not alter its colour

Without acids

Without alcalis

Without cloruro metileno

TECHNICAL CHARACTERISTICS

Referencia Color QUITAMONT GEL

Finish Transparent

Specific weight 0,96 ± 0,05 kg/l

Viscosity 44 +/- 5 PO

Solids in volume 3 ± 1

Solids in weight 3 ± 1

Aproximated performance by coat 3-6 m²/L

Dry to repaint (20°C HR:60%):6h

Colours Translucent, milky white

SURFACE PREPAIRING**New surfaces**

Not applicable

Restoring and maintenance

See the following Application section.

WAY OF USE**Application notes**

1. Homogenise the product slowly using a spatula.

2. Apply with brush or spatula, depending on the thickness of coat to be stripped, leave to act for between 10 and 20 minutes.

3. Remove softened paint with scraper or brush.

Fecha de Alta

17-01-2011

Versión

8 - 23/08/2024

4. We strongly recommend testing the product on a small area before use to ensure suitability. If you have any questions, please consult the Technical Department.

5. Prior to repainting we recommend cleaning thoroughly with clean water and allowing to dry.

Solvent for dilution and cleaning

Water

Way of use Aproximate dilution

Painting brush

Uso

Roller

Uso

Pallette / spatula

Uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Montoxyl range			
MAX	No suele ser necesario		Sistema Gama madera familia 5
STD	No suele ser necesario		Sistema Gama madera familia 5
Polyurethane lacquers and varnishes			
MAX	Quitamont gel	Quitamont gel	Sistema Gama Madera familia 5
STD	Quitamont gel		Sistema Gama Madera familia 5
Nitrocellulose lacquers and varnishes			
MAX	Quitamont gel	Quitamont gel	Sistema Gama Madera familia 5
STD	Quitamont gel		Sistema Gama Madera familia 5
Enamels and synthetic varnishes			
MAX	Quitamont gel	Quitamont gel	Sistema Gama Madera Familia 5
STD	Quitamont gel		Quitamont gel
Paints and watter lasures			
MAX	Quitamont gel	Quitamont gel	Sistema Gama Madera Familia 5
STD	Quitamont gel		Quitamont gel

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

503512

QUITAMONT GEL



Fecha de Alta

17-01-2011

Versión

8 - 23/08/2024

PACKINGS

0.375 L, 0.75 L, 4 L