

503530

Fecha de Alta

01-01-1900

Versión

6 - 29/05/2024

QUITAMONT LIMPIA-PINTADAS

MONTÓ
profesional**FAMILY
LINE****PRODUCTOS PARA USO ESPECIFICO
SISTEMA ANTIGRAFFITI****DESCRIPTION AND NATURE**

Paint removal gel which easily removes graffities, synthetic enamels and plastic paints from products of Montó brand that are considered anti-graffiti (for example Acripol Barniz).

USAGES

Use over Antipintadas Monto

PROPERTIES

High performance

Do not change the product added with Antipintadas Monto

At least it will soften the painting, making more easy to remove it with pressured water to be removed with water

It reduces maintenance cost

TECHNICAL CHARACTERISTICS

Referencia Color QUITAMONT LIMPIA-PINTADAS

Finish Transparent

Aproximated performance by coat Depending of product usage

Colours Colorless

SURFACE PREPAIRING**New surfaces**

New surfaces:

Not necessary. After application, remove with plenty of water

Restoring and maintenance

Not necessary. After application, remove with plenty of water

WAY OF USE**Application notes**

Use undiluted with a cloth, rag or similar, brush or roller.

Rub until the paint is removed

Then rinse with plenty of water until all traces have been removed

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Ensure the area is well ventilated while the product is drying.

Solvent for dilution and cleaning**Way of use**

Painting brush

Roller

Cloth

Aproximate dilution

0

0

0

QUITAMONT LIMPIA-PINTADAS

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Monto anti-graffiti paints			
MAX	Quitamont Limpia Pintadas	Quitamont Limpia Pintadas	Quitamont Limpia Pintadas
STD			

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS