

Fecha de Alta

13-08-2021

Versión

4 - 19/08/2024

**FAMILY**
LINE

ESMALTES

SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

High-quality spray paint for application on radiators. For beautifying and repairing radiators and their pipes. Particularly suitable for surfaces exposed to temperature variations.

USAGES

Indoors
Radiators
After correct priming
Iron

PROPERTIES

Fast drying
Resistance to cleaning products
Very robust and resistant
Excellent mechanical resistance
Excellent covering
Good anti-corrosive power
Smooth and fine finish
Withstands temperatures up to 80°C

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY RADIADORES SATIN
Aproximated performance by coat	Depending of product usage

Dry to touch	30min
Dry to repaint	24h
Colours	Satin white and Matt White

SURFACE PREPAIRING**New surfaces**

Iron, derived metals and other metals

-The surface must be free of foreign products and/or residues.

-The surface must be degreased, clean and dry.

-On rusty surfaces, we must eliminate the rust by the usual means recommended by Montó with any rust inhibitor manufactured by our Company, which should be applied in advance.

-We must protect the areas that we do not want to paint.

-Eliminate, in general, products that are poorly adhered or in poor condition

Restoring and maintenance

Iron and enamelled derivatives:

1. On paints in good condition, sand to open the pore, checking that the adherence is perfect.

2. On paints in bad condition, remove it by mechanical or chemical means and proceed as if it were a new surface.

WAY OF USE**Application notes**

Shake the container vigorously for about 2 minutes to homogenise its contents perfectly.

Carry out application tests in a non-visible place.

Protect areas that are not to be painted.

Fecha de Alta

13-08-2021

Versión

4 - 19/08/2024

Apply at a distance of 25-30cm from the surface in light, criss-cross strokes.
 Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.
 Maintain good ventilation conditions during the drying time.
 Do not apply while the relative humidity is above 80%.
 Do not use at temperatures below 15°C.
 When finished, empty the contents of the cannula by dosing with the container upside down.
 Approximate yield per 400ml container 0,8 - 1,2 m2 (two cross-coats)

Solvent for dilution and cleaning

Solvent 1406-05

Way of use

Aproximate dilution

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Metal			
MAX	Montospray Primer Universal	Montospray Radiadores	Montospray Radiadores
STD	Montospray Radiadores		Montospray Radiadores
Old paintings in good condition			
MAX	Montospray Primer Universal	Montospray Radiadores	Montospray Radiadores
STD	Montospray Radiadores		Montospray Radiadores

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water.
 Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C.
 For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L