

Fecha de Alta

14-09-2021

Versión

3 - 19/08/2024

**FAMILY**
LINE

ESMALTES

SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

Marking paint for works, for fast and accurate marking and lettering on asphalt, concrete, masonry, pavers, wood, earth, stone, etc.

USAGES

Indoors/Outdoors

Wood

Construction

Ground

PROPERTIES

Fast drying

Easy to apply and repaint

Adhesion on wet surfaces

High level of coverage.

TECHNICAL CHARACTERISTICS

Referencia Color MONTOSPRAY MARCAJE AMARILLO

Aproximated performance by coat Depending of product usage

Dry to touch 30min

Dry to repaint 24h

Colours Yellow 201, Red 202

SURFACE PREPAIRING**New surfaces****Restoring and maintenance****WAY OF USE****Application notes**

Shake the container for approximately 3 mins.

Does not need cleaning due to its exclusive self-cleaning system.

Apply at a distance of between 5 and 15cm.

The 500ml container can mark up to a total of 220m.

Solvent for dilution and cleaning

Solvent 1406-05

Way of use**Aproximate dilution**

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Asphalt			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje
Wood			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje
Works			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L