

**FAMILY**

ESMALTES

LINE

SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

Special acrylic-based anti-stain spray paint. Suitable for sealing most stains such as nicotine, oil, moisture stains, tomato sauce, wine, tea, coffee...

USAGES

Indoors/Outdoors

Gypsum Board

Cement

Plaster

Dripping effect

Construction

Plaster

PROPERTIES

Anti-spots

Smooth finish

Fast action

Good hiding power capacity

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY ANTIMANCHAS BLANCO
Aproximated performance by coat	Depending of product usage
Dry to touch	15min
Dry to repaint	1h

SURFACE PREPAIRING**New surfaces**

The surface must be clean and free of dust, oils and non-adherent materials. Use suitable solvents for cleaning.

If the surface is very absorbent, more coats of the product will be necessary.

Do not apply on fresh stains.

Restoring and maintenance

How to remove stains:

This will depend on the absorption level of the surface. Do not apply on fresh stains.

On nicotine, tea, coffee and water-based marker stains: apply minimum 2 cross-coats, allowing 10 minutes drying time between each one. Leave to dry for 24hrs and repeat if necessary.

On oil stains, tomato sauce, wine, vinegar, pencils and solvent-based markers: apply minimum 2 cross-coats, allowing 10 minutes drying time between each one. Leave to dry for 24hrs and repeat if necessary.

On lipstick stains: Wash the stained area with a damp cloth. Allow to dry and then apply minimum 2 cross-coats, allowing 10 minutes drying time between each coat. Leave to dry for 24hrs and repeat if necessary.

On soot stains: Wash the stained area with a damp cloth. Allow to dry and then apply minimum 2 cross-coats, allowing 10 minutes drying time between each coat. Leave to dry for 24hrs and repeat if necessary.

WAY OF USE**Application notes**

Use the spray at 20-25°C. In cold temperatures, heat in a bain-marie, never in direct contact with flame.

Shake the spray for 1 to 2 minutes to ensure good homogenisation.

To ensure proper application, it is recommended to shake the product during use.

Fecha de Alta

13-08-2021

Versión

3 - 17/09/2024

Spray at 25-30cm away from the surface

Apply by crossing the coats, first vertically and then horizontally.

Approximate yield per 400ml container 1 - 2 m2 (two cross-coats)

Solvent for dilution and cleaning

Solvent 1406-05

Way of use**Aproximate dilution****SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
Stained support			
MAX	Montospray Antimanchas	Montospray Antimanchas	Acabados Montó
STD		Montospray Antimanchas	Acabados Montó

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L