

PLASMONT BRICOLAGE ESCAYOLA PLASTICA



FAMILY PREPARACIONES, FONDOS E IMPR.

LINE MASILLAS EN POLVO

DESCRIPTION AND NATURE

Powder plaster of great hardness, withness and smooth finish. For small repairs of mouldings, manual works and mouldings. Quick setting.

USAGES

Indoors
Plaster finishing
Manual Works

PROPERTIES

Whiteness
Does not decrease
Fast sanding
Good adhesion
Fast hardening
Very fine gross
Very smooth finishes without sanding
Drying fast
Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT BRICOLAGE ESCAYOLA PLASTICA
Finish	Matt
Specific weight	2,25± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to repaint	(20°C HR: 60%): 24 days
Colours	White

SURFACE PREPARING

New surfaces

Plaster and mortar cement:

- Test putty suitability on surface.
- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be treated to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface.
- Remove off any resulting dust by brushing and apply putty as indicated under Application Systems and Application points.
- Do not apply products in extremely thick layers.
- For extremely damaged surfaces, use suitable fixer (see family 6): Emulsion Fijadora, fijamont or Fijalite before applying putty.

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems. Test adherence level and treat as per new surfaces.

WAY OF USE

Application notes

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Surfaces should be anchored properly.
- Repaint only after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
- Can be dried mechanically.
- Ovaldine, Montoplastica, Montoature, Esmalte Montosintetic, Luxatin and Select Decoration products are suitable for top coats.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel
Pallette / spatula
Pallette

Aproximate dilution

500ml de agua por kg de escayola
500ml de agua por kg de escayola
500ml de agua por kg de escayola

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX			
STD	Escayola plástica	Fijador	Familia 1, 4, 12

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE


Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg

PLASMONT BRICOLAGE ESCAYOLA PLASTICA



FAMILY LINE

DESCRIPTION AND NATURE

Powder plaster of great hardness, withness and smooth finish. For small repairs of mouldings, manual works and mouldings. Quick setting.

USAGES

PROPERTIES

Whiteness
Does not decrease
Fast sanding
Good adhesion
Fast hardening
Very fine gross
Very smooth finishes without sanding
Drying fast
Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	2,25± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to repaint	(20°C HR: 60%): 24 days
Colours	White

SURFACE PREPARING


New surfaces

Plaster and mortar cement:

- Test putty suitability on surface.
- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be treated to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface.
- Remove off any resulting dust by brushing and apply putty as indicated under Application Systems and Application points.
- Do not apply products in extremely thick layers.
- For extremely damaged surfaces, use suitable fixer (see family 6): Emulsion Fijadora, fijamont or Fijalite before applying putty.

Restoring and maintenance

Remove off any remains or peeling of paint or any other foreign products. Open pore by sandpapering or any other mechanical systems. Test adherence level and treat as per new surfaces.



WAY OF USE

Application notes

- For its thinning, use only fresh, clean water.
- Use only indicated tools under "Application Systems", clean and rust-free.
- Surfaces should be anchored properly.
- Repaint only after indicated drying time, which depends on moistening and temperature conditions as well as layer thickness.
- Can be dried mechanically.
- Ovaldine, Montoplastica, Montoature, Esmalte Montosintetic, Luxatin and Select Decoration products are suitable for top coats.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel
Pallette / spatula
Pallette

Aproximate dilution

500ml de agua por kg de escayola
500ml de agua por kg de escayola
500ml de agua por kg de escayola

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX			
STD	Escayola plástica	Fijador	Familia 1, 4, 12

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

1 Kg